

Date: November 9, 2009

Number: TAB-09-012

To: North American Sales Channel

**Notice: Disabling Ethernet Communications on the TL260GS/TL265GS**

The purpose of this bulletin is to detail how to disable the Ethernet portion of the TL260GS and TL265GS dual-path communicator. This change will result in the product being a 'GSM only' communicator with no troubles related to lack of Ethernet connectivity.

When configuring the unit via Connect 24 you must enter in a receiver IP address of 000.000.000.000 for both Receiver 1 and Receiver 2 to disable Ethernet functionality.

Ethernet Option Group			
	DNIS	Account Code	
Receiver 1 Account	00000	5489	
Receiver 2 Account	00000	5489	
	IP	Local Port	Remote Port
Receiver 1	0.0.0.0	0	0
Receiver 2	0.0.0.0	0	0
	IP	Subnet Mask	Gateway
Ethernet	0.0.0.0	0.0.0.0	0.0.0.0
DLS Outgoing Local Port	0	DLS Incoming Local Port	0
DHCP	<input checked="" type="checkbox"/>	Periodic Test Transmission Interval	None

**NOTE:** If the communicator has already been activated only Connect 24, a Master Reseller, or a Dealer with appropriate login credentials may change the receiver information.

Communications

To order, contact your Order Entry Account Representative: 1-888-888-7838.  
For more information on this product or other DSC products, email [info@dsc.com](mailto:info@dsc.com) or contact your local Sales Representative or Technical Support.